

ALTEMA OIL

Product

Data Sheet

ALTEMA PRO FLEET 15W40 API SJ/CH4 Multigrade Motor Oil

DESCRIPTION

ALTEMA Pro Fleet 15W40 API SJ/CH4 is an ultra-modern mineral engine oil incorporating a special blend of base stocks formulated using the latest unique technology which provides maximum engine power. It is designed for the lubrication of the most diesel engines with turbocharging and injection pumps. It meets or exceeds the requirement of SJ/CH4 or lesser specification engine oil. It provides a high level of protection against wear, sludge deposit and acid attack.

APPLICATION

- For petrol and diesel engines

BENEFITS

- Ultimate Protection - protects mechanical parts and fully preserves engine power in all driving conditions.
- Synthetic Technology - performs better than conventional oil and can satisfy OEM extended drain interval requirements due to excellent oxidation resistance.
- Advanced detergency and dispersancy - advanced detergent and dispersive additive technology keeps engine parts clean.

Fuel Efficient - low viscosity, rapid oil flow and low friction effectively contribute towards easy cold starts and reducing fuel consumption.

PERFORMANCE STANDARDS

ALTEMA PRO FLEET 15W40 API SJ/CH4 is suitable for use where the following specifications apply,

API SJ/CH4
MB 228.3
MAN 3275
VOLVO VDS
MACK EOM
ALLISON C-3



www.altema.co.za / eben@maxwax.co.za /

BRACKENFELL

ALTEMA OIL

Product

Data Sheet

ALTEMA PRO FLEET 15W40 API SJ/CH4 Multigrade Motor Oil

PHYSICAL CHARACTERISTICS

SAE Viscosity Grade		15W-40
Cinematic Viscosity @ 40°C	cSt	96.31
Kinematic Viscosity @ 100°C	cSt	14.37
Viscosity Index		154
Pour Point	°C	-33
Flash Point (PMCC)	°C	215
TBN	mgKOH/gm	8.9
Density @ 20°C	kg/l	0.875



www.altema.co.za / eben@maxwax.co.za /

BRACKENFELL